

**SWISSDIS**



Swissdis AG  
Grasweg 7  
CH-4911 Schwarzhäusern

Tel.: +41 62 919 44 00  
Fax: +41 62 919 44 01  
[info@swissdis.ch](mailto:info@swissdis.ch)  
[www.swissdis.ch](http://www.swissdis.ch)



# SPECIFICATIONS

## US0402R LED Chip 0402 Red

Version April 2017

# Unilite Opto Technology

email: [info@unilite-tech.com](mailto:info@unilite-tech.com)

## U-S0402R-P&S



### ■ Description

The SMD type U-S0402R-P&S 1 chips LED, with its light weight and smaller than lead frame type components, enables smaller board size, higher packing density, reduced storage space and miniature applications.

- Dice Material : AlInGaP
- Light Color : Red
- Lens Color : Diffused

### ■ Features

- 1 chips package
- Compatible with automatic placement equipment
- Compatible with reflow soldering process
- Long operating life
- Low forward voltage operated
- Instant light
- Pb -free/ RoHS compliant
- 4K/Reel

### ■ Applications


- Information boards
- Automotive Interior Lighting
- Indoor and outdoor display
- Indicator
- Backlighting
- General applications

# Unilite Opto Technology

email: [info@unilite-tech.com](mailto:info@unilite-tech.com)


## U-S0402R-P&S

### ■ Outline Dimensions ( mm )



Tolerance :  $\pm 0.1$  mm


### ■ Recommended Soldering Pad Design



Tolerance :  $\pm 0.1$  mm

### ■ Part Numbering System

**U - S 0 4 0 2 R - P&S**



# Unilite Opto Technology

email: [info@unilite-tech.com](mailto:info@unilite-tech.com)

## U-S0402R-P&S

### ■ Absolute Maximum Ratings at Ta = 25 °C

PARAMETER	symbol	MAX.	UNIT
Power Dissipation *	PD	48	mW
Continuous Forward Current *	IF	20	mA
Peak Forward Current ( 1/10 Duty Cycle , 0.1ms Pulse Width ) *	IFP	40	mA
Electrostatic Discharge	ESD	2000	V
Operating Temperature Range	Topr	-40 to + 85	°C
Storage Temperature Range	Tstg	-40 to + 90	°C
Reflow Soldering Condition	Tsld	265 °C for 5 sec.	

### ■ Electro-Optical Characteristics

Red , Ta = 25°C, IF=20mA

PARAMETER	SYMBOL	VALUES			UNIT
		MIN.	TYP.	MAX.	
Luminous Intensity	IV	112.5	180	285	mcd
Forward Voltage	Vf	2		2.6	V
View angle	2θ 1/2		120		Deg
Peak Wavelength	λp		632		nm
Dominant Wavelength	λd	615	624	635	nm
Reverse Current, VR= 5V	IR			10	μA

### ■ Bin Code

Unit: mcd@20mA

Bin Code		IV	
		Min	Max
Red	R1	112.5	180
	R2	180	285

Note: It maintains a tolerance of +/- 10% on Luminous Intensity


# Unilite Opto Technology

email: [info@unilite-tech.com](mailto:info@unilite-tech.com)


**U-S0402R-P&S**

## ■ Typical Electro-Optical Characteristics Curve


Relative Intensity VS. Wavelength




Relative Intensity vs. Forward Current




Forward Current VS Soldering Temperature



Forward Voltage vs. Forward Current



Directive Characteristics




# Unilite Opto Technology


email: [info@unilite-tech.com](mailto:info@unilite-tech.com)

## U-S0402R-P&S

■ Carrier Type Dimensions  
Q'ty: 4000pcs/ Reel



■ Reel Dimensions



# Unilite Opto Technology

email: [info@unilite-tech.com](mailto:info@unilite-tech.com)

## U-S0402R-P&S

### ■ Reliability Test Items and Conditions

(1)TEST ITEMS AND RESULTS

Test Item	Standard Test Method	Test Conditions	Note	Number of Damaged
Thermal Shock	MIL-ST-	-40°C ~ 105°C 10min. 10min.	100 cycles	0/20
	MIL-ST-			
	MIL-ST-			
Temperature Cycle	MIL-ST-	105°C ~ 25°C ~ -55°C ~ 25°C 30min. 5min. 30min. 5min.	10 cycles	0/20
	MIL-ST-			
	MIL-ST-			
	JIS C 7021:A-4			
High Temperature Storage	MIL-STD-	Ta=105°C +/- 5°C	1000 hrs.	0/20
	JIS C 7021:B-10			
Low Temperature Storage	JIS C 7021:B-12	Ta=-40°C +/-5°C	1000 hrs.	0/20
Steady State Operating Life	MIL-STD-	Ta=25°C, I <sub>F</sub> =20mA, DC	1000 hrs.	0/20
	MIL-STD-			
	JIS C 7021:B-1			
High Temperature &High Humidity Storage Test	MIL-ST-202F:103B JIS C 7021:B-11	Ta=65°C +/- 5°C, RH=90-95%,	1000 hrs.	0/20
Solerability Test	MIL-ST-	T. Sol:235°C +/- 5°C	10 cycles	0/20
	MIL-STD-	Immersion Time 2+/- 0.5sec		
	MIL-STD-	Coverage ≥ 95% of the dipped surface		
	IEC 68 Part 2-20			
	JIS C 7021:A-2			
IR Reflow	MIL-STD-750D:2031.2	T=260C Max, 10 sec Max,		
	J-STD-020	Time= 6min		

# Unilite Opto Technology

*email: info@unilite-tech.com*

## U-S0402R-P&S

### ■ Cautions

#### (1) Moisture Proof Package

- A) The moisture proof package, a plastic bag with a zipper, is used to keep moisture to a minimum in the package.
- B) A package of a moisture absorbent material (silica gel) is also inserted into the plastic moisture proof bag and the silica gel changes its color from blue to pink as it absorbs moisture.
- C) The absorbed moisture in the SMT package may vaporize and expand during soldering. This may cause exfoliation of the contacts and damage to the optical characteristics of the LEDs.

#### (2) Storage Conditions

- A) Before opening the package :  
The LEDs should be kept at 30°C or less and 45~60% RH or less and should be used within a year. When storing the LEDs, moisture proof package with absorbent material (silica gel) is recommended.
- B) After opening the package :  
The LEDs should be kept at 30°C or less and 55% RH or less and should be soldered within 168 hours (7days) after opening the package. The unused LEDs should be stored in moisture proof packages.
- C) It's also recommended to return the LEDs to the original moisture proof bag and to reseal the moisture proof bag again.
- D) If the moisture absorbent material (silica gel) has faded away or the SMD LEDs have exceeded the storage time, baking treatment ( more than 24 hours at 65+/-5°C ) should be performed before soldering.

#### (3) Heat Generation

- A) The thermal design of the end product is very important. It is necessary to avoid intense heat generation and operate within the maximum ratings given in this specification.
- B) The operating current should be decided after considering the ambient maximum temperature of LEDs.

#### (4) Cleaning

- A) Isopropyl alcohol is recommended to be used as a solvent for cleaning the LEDs.
- B) Before cleaning, a pre-test should be done to confirm whether any damage to the LEDs will occur.



# Unilite Opto Technology

email: [info@unilite-tech.com](mailto:info@unilite-tech.com)


## U-S0402R-P&S

### (5) Soldering


Reflow Soldering ( recommended ) :

- A) To prevent from cracking, please bake ( 65°C , 24hrs ) before soldering.
- B) When soldering, do not load stress on the LEDs during heating.
- C) Never take next process until the component is cooled down to room temperature after reflow.
- D) After soldering, do not warp the circuit board.
- E) The recommended reflow soldering profile ( measuring on the surface of the LED resin ) is the following:

#### (a) Lead-Free Solder



#### (b) Lead Solder



Manual Soldering ( not recommended ) :

- A) To prevent from cracking, please bake ( 65°C , 24hrs ) before soldering.
- B) Temperature at tip of iron: 250°C Max. ( 25W ).
- C) It's banned to load any stress on the resin during soldering.
- D) Soldering time: 3 sec. Max.( one time only ).

# Unilite Opto Technology

*email: info@unilite-tech.com*

## U-S0402R-P&S

- (6) ESD ( electrostatic discharge ) protection ( base on machine mode )
- A) The product is Gallium Nitride ( GaN ) based light emitting diode ( LED ) and is extremely sensitive to ESD. Users are strongly recommended to take necessary meter to test the static electricty and avoid ESD when handling this product.
  - B) Proper grounding of machines ( via  $1M\Omega$  ), using static dissipative mats, containers, working uniforms and shoes are considered to be effective against ESD.
  - C) An ionizer is recommended in the facility or environment where ESD may be generated easily, and soldering iron with a grounded tip is also recommended.
  - D) When inspecting the final products in which LEDs are assembled, it is recommended to check whether the assembled LEDs are damaged by ESD or not. It is simple to find damaged LEDs by light-on or VF test at lower current ( below 1mA is recommended ).
  - E) ESD damaged LEDs will show some unusual characteristics such as the remarkable increasing of leak current, the decreasing of forward voltage, or the LEDs do not light on at the low current.
- (7) Other
- A) Care must be taken to ensure that the reverse voltage will not exceed the absolute maximum rating when using the LEDs with matrix drive.
  - B) The LED light output is strong enough to injure human eyes. Precaution must be taken to prevent looking directly at the LEDs with unaided eyes for more than a few seconds.
  - C) The LEDs described here are intended to be used for ordinary electronic equipment, please consult Unilite Opto in advance for information on applications.
  - D) Installing a protection device in the LED driving circuit to avoid surge current exceeding the max rating during on/off switching.
  - E) The appearance and specifications of the product may be modified for improvement without notice.
  - F) Please use the product within 168 hours after opening the seal and keep under  $30\text{ }^{\circ}\text{C}$  and 70% humidity.
  - G) Unilite Opto Technology will not be responsible for any claim for damage if the user use the product without following the caution or instruction of the specification.